



# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 8-4-2011 Revision date: 27-11-2020 Supersedes: 26-10-2020 version: 3.4

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic  
Product code : 53000

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Use of the substance/mixture : Automotive care products  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

MPM International Oil Company BV  
Cyclotronweg 1  
2629 HN Delft - Nederland  
T +31 (0)15 2514030  
[info@mpmoil.com](mailto:info@mpmoil.com) - [www.mpmoil.com](http://www.mpmoil.com)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Show CLP information only

Not classified

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Comments : Highly refined mineral oil, contains <3% (w/w) DMSO extract, according to IP346

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates(petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 10 – ≤ 24	Asp. Tox. 1, H304
Bis(nonylphenyl)amine	CAS-No.: 36878-20-3 EC-No.: 253-249-4 REACH-no: 01-2119488911-28	≥ 1 – ≤ 2,4	Aquatic Chronic 4, H413
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 EC Index-No.: 272-028-3 REACH-no: 01-21419543726-33	≥ 0,1 – ≤ 0,99	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

#### Specific concentration limits

Name	Product identifier	Specific concentration limits
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 EC Index-No.: 272-028-3 REACH-no: 01-21419543726-33	(6,25 ≤ C < 100) Skin Irrit. 2, H315 (10 ≤ C < 12,5) Eye Irrit. 2, H319 (12,5 ≤ C < 100) Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

After inhalation : Not required.  
After skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.  
After eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.  
After ingestion : If swallowed, seek medical advice immediately and show this container or label. Rinse mouth out with water. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

After inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.  
After skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

After eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
After ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO <sub>2</sub> .
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: No additional information available.
-------------	--

### 5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

#### 6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

### 6.2. Environmental precautions

Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Alkaline cleaner. Sand or other absorbent.
Other information	: Spill area may be slippery.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Handling temperature	: < 40 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage temperature	: < 40 °C
---------------------	-----------

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Storage area : Store in a closed container. Keep in a cool, well-ventilated place.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

No additional information available

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m<sup>3</sup> oilspray (TWA, 8 hour workday) is recommended.

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Technical measures:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Gloves. Safety glasses.

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety goggles

##### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Wear suitable gloves resistant to chemical penetration

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)	>0,35		

##### Other skin protection

##### Materials for protective clothing:

Wear suitable protective clothing, gloves and eye/face protection

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: Red.
Appearance	: Oily.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 200 °C ASTM D 92
Auto-ignition temperature	: No data available.
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 95 mm <sup>2</sup> /s
Solubility	: Slightly soluble, the product remains on the water surface.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 854 kg/m <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions of use.

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

None under normal conditions.

### 10.5. Incompatible materials

Oxidizing agent. Acids and bases.

### 10.6. Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, nitrogen oxides (NO<sub>x</sub>), sulphur compounds.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Bis(nonylphenyl)amine (36878-20-3)

LD50 oral rat	> 5000 mg/kg OECD 401
LD50 oral	> 2000 mg/kg OECD 402

#### Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)

LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	> 3160 mg/kg bodyweight OECD 402
LC50 Inhalation - Rat	> 2 mg/l > 2 ml 1h OECD 403 read across
ATE CLP (oral)	2600 mg/kg bodyweight

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

#### MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

Viscosity, kinematic	95 mm <sup>2</sup> /s
----------------------	-----------------------

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 11.2.2. Other information

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Bis(nonylphenyl)amine (36878-20-3)	
LC50 fish 1	> 100 mg/l OECD 203 (Danio rerio @96h)
EC50 Daphnia 1	> 100 mg/l OECD 202 (Daphnia magna)
EC50 72h - Algae [1]	> 100 mg/l OECD 201 (Desmodesmus subspicatus)

  

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)	
LC50 fish 1	4,5 mg/l OECD 203 (Oncorhynchus mykiss) 96h
EC50 Daphnia 1	5,4 mg/l OECD 202 (Daphnia magna) 48h
EC50 72h - Algae [1]	2,1 mg/l Selenastrum capricornutum UTEX 1648

### 12.2. Persistence and degradability

MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic	
Persistence and degradability	Not soluble in water, so only minimally biodegradable.

  

Bis(nonylphenyl)amine (36878-20-3)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	1 % @28d

  

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)	
Biodegradation	1,5 % OECD 301B 28d

### 12.3. Bioaccumulative potential

Bis(nonylphenyl)amine (36878-20-3)	
Log Pow	> 7,6
Bioaccumulative potential	Bioaccumulation possible.

  

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)	
Log Pow	0,9 @23C

### 12.4. Mobility in soil

Bis(nonylphenyl)amine (36878-20-3)	
Soil	Adsorbs into the soil.

  

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)	
Soil	Adsorbs into the soil.

### 12.5. Results of PBT and vPvB assessment

No additional information available

# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The product does not contain any substances with endocrine disrupting properties.

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.

## SECTION 14: Transport information

In accordance with ADR / IMDG

### 14.1. UN number or ID number

UN-No. : Not applicable  
UN-No. (IMDG) : Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable

### 14.3. Transport hazard class(es)

**ADR**  
Transport hazard class(es) (ADR) : Not applicable

**IMDG**  
Transport hazard class(es) (IMDG) : Not applicable

### 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

**Overland transport**  
No data available

**Transport by sea**  
No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable



# MPM 2-Stroke Gear Oil 10W-40 Semi-Synthetic

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No additional information available

### SECTION 16: Other information

#### Full text of H- and EUH-statements

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Irrit. 2	Skin corrosion/irritation, Category 2

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.