



16000HFM ATF Automatic Transmission Fluid HFM

Document version: May 13, 2024



Description

This premium synthetic automatic transmission oil has been specially developed for all Audi, VW, Porsche, Volvo, Toyota, Lexus and Saab models (amongst others) fitted with an Aisin Warner automatic transmission.

According to the specifications of

Aisin Warner JWS 3309 / JWS 3314 / JWS 3317
BMW ETL-7045E / ETL-8072B
Fiat 9.55550-AV1
Ford Mercon-V / WSS-M2C202-B
Honda ATF Z1
Hyundai ATF SP-III / ATF SP-IV
KIA SP-III / SP-IV
Mitsubishi Diamond SP-II / Diamond SP-III
Nissan Matic D / Matic J / Matic K
Opel/GM 1940 773
Saab JWS 3309
Suzuki JWS 3309
Toyota T / T-III / T-IV
VW G 055 025
Volvo 1161540

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 16001HFM | 1 L | 6 | 450 |
| 16004HFM | 4 L | 4 | 112 |
| 16020HFM | 20 L | 1 | 30 |
| 16060HFM | 60 L | 1 | 6 |
| 16205HFM | 205 L | 1 | 2 |
| 16999HFM | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|-------------------------------|-------|--------------------|--------|
| Density at 15°C | 0.849 | kg/l | |
| Colour | red | | |
| Viscosity | 10W | | |
| Kinematic Viscosity at 40°C | 35.6 | mm ² /s | |
| Kinematic Viscosity at 100°C | 8.1 | mm ² /s | |
| Viscosity Index | 212 | | |
| Brookfield Viscosity at -40°C | 12000 | mPa.s | |

These characteristics are typical of current production. Variations in these characteristics may occur.